

WOJET®

Hose Reel **OPERATION MANUAL**

Part No.: AE2017



NINGBO HIJET CLEANING EQUIPMENT CO., LTD

Add: No.618 Dongming Road, Zhenhai Economic Development Zone,
Ningbo, CHINA 315221

Tel: 86-574-26289620 Fax: 86-574-26251988

E-mail: info@hijet.com.cn

SERVICE CENTER: ROYAL PALM BEACH FL 33421

Tel: (561)249-2830 Fax: (561)249-2871

Hose Reel AE2017

Specifications:

Capacity: 50feet of 3/8" hose(AE2017)

Inlet: 3/8" MNPT

Outlet: 3/8" FNPT

Maximum Pressure: 4000PSI / 275Bar

Maximum Temperature: 150°C / 302°F



Read the following precautions and instructions before you begin assembly or using. Keep these instructions in a dry place for future reference.

Safety Precautions

1. Make sure incoming pressure does not exceed the rated pressure.
2. Use the proper eye protection when assembling and using the hose reel.
3. Assemble the hose reel on a clean workbench free of debris and water.
4. Use soap and water when checking for air leaking.
5. Keep children away from the work area.

Warning: Exposure of skin directly to pressurized air or fluids could result in severe body injury.

Installation and Assembly

Noted: You will need to prepare appropriate hardware for mounting your new hose reel. Holes have been provided in the reel base, for mounting on a suitable flat surface. You will also need to prepare hose for the reel. Refer to specification information to determine the correct hose length.



Spring Locking Clip



High Pressure Swivel



3/8" FNPT Outlet



Anti Rewind Block